

AS/NZS IEC 60479.1:2022  
IEC 60479-1:2018



Australian/New Zealand Standard™

# Effects of current on human beings and installations

[This is a preview. Click here to purchase the full publication.](#)

Part 1: General aspects



AS/NZS IEC 60479.1:2022

This Joint Australian/New Zealand Standard™ was prepared by Joint Technical Committee EL-001, Wiring Rules. It was approved on behalf of the Council of Standards Australia on 3 March 2022 and by the New Zealand Standards Approval Board on 2 March 2022.

This Standard was published on 25 March 2022.

The following are represented on Committee EL-001:

Australian Building Codes Board  
Australian Energy Council  
Australian Industry Group  
Communications, Electrical and Plumbing Union — Electrical Division  
Consumers Federation of Australia  
Electrical Regulatory Authorities Council  
Electrical Safety New Zealand  
Electrical Workers Registration Board  
ElectroComms & Energy Utilities Industry Skills Council  
Energy Networks Australia  
Engineers Australia  
Engineering New Zealand  
Institute of Electrical Inspectors

**This is a preview. Click here to purchase the full publication.**

National Electrical and Communications Association  
National Electrical Switchboard Manufacturers Association  
WorkSafe New Zealand  
The Manufacturers' Network

This Standard was issued in draft form for comment as DR AS/NZS IEC 60479.1:2021.

### **Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

[www.standards.org.au](http://www.standards.org.au)

[www.standards.govt.nz](http://www.standards.govt.nz)

ISBN 978 1 76113 696 2

Australian/New Zealand Standard™

# Effects of current on human beings and livestock

**This is a preview. Click here to purchase the full publication.**

## Part 1: General aspects

Originated as part of MP 30—1976.  
Revised and redesignated AS 3859—1991.  
Jointly revised and redesignated in part as AS/NZS 60479.1:2002.  
Previous edition 2010.  
Third edition 2022.



© IEC Geneva Switzerland 2022 — All rights reserved  
© Standards Australia Limited/the Crown in right of New Zealand, administered by the New Zealand Standards Executive 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of either the IEC or the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth) or the Copyright Act 1994 (New Zealand). If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please see the contact details on the back cover or the contact us page of the website for further information.

## Preface

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-001, Wiring Rules, to supersede AS/NZS 60479.1:2010.

The objective of this document is to provide basic guidance on the effects of shock current on human beings and livestock.

For a given current path through the human body, the danger to persons depends mainly on the magnitude and duration of the current flow. However, the time/current zones specified in the following clauses are, in many cases, not directly applicable in practice for designing measures of protection against electrical shock. The necessary criterion is the admissible limit of touch voltage (i.e. the product of the current through the body called touch current and the body impedance) as a function of time. The relationship between current and voltage is not linear because the impedance of the human body varies with the touch voltage, and data on this relationship is therefore required. The different parts of the human body (such as the skin, blood, muscles, other tissues and joints) present to the electric current a certain impedance composed of resistive and capacitive components.

The values of body impedance depend on a number of factors and, in particular, on current path, on touch voltage, on the duration of contact, and on the condition of the body. **This is a preview. Click here to purchase the full publication.**

The impedance values indicated in this document result from a close examination of the experimental results available from measurements carried out principally on corpses and on some living persons.

Knowledge of the effects of alternating current is primarily based on the findings related to the effects of current at frequencies of 50 Hz or 60 Hz which are the most common in electrical installations. The values given are, however, deemed applicable over the frequency range from 15 Hz to 100 Hz, threshold values at the limits of this range being higher than those at 50 Hz or 60 Hz. Principally the risk of ventricular fibrillation is considered to be the main mechanism of death of fatal electrical accidents.

This basic safety publication is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51. It is not intended for use by manufacturers or certification bodies.

This document is identical with, and has been reproduced from, IEC 60479-1:2018, *Effects of current on human beings and livestock — Part 1: General aspects*.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker. Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

## NOTES

**This is a preview. Click here to purchase the full publication.**

## CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references .....	10
3 Terms and definitions .....	10
3.1 General definitions.....	10
3.2 Effects of sinusoidal alternating current in the range 15 Hz to 100 Hz .....	11
3.3 Effects of direct current.....	12
4 Electrical impedance of the human body and livestock .....	13
4.1 General.....	13
4.2 Internal impedance of the human body ( $Z_i$ ) .....	13
4.3 Impedance of the skin ( $Z_s$ ).....	13
4.4 Total impedance of the human body ( $Z_T$ ) .....	13
4.5 Factors affecting initial resistance of the human body ( $R_0$ ) .....	14
4.6 Total body impedance dependence for large, medium and small surface areas of contact.....	14
4.6.1 Sinusoidal alternating current 50/60 Hz for large surface areas of contact .....	14
4.6.2 Sinusoidal alternating current 50/60 Hz for medium and small surface areas of contact.....	17
4.6.3 Sinusoidal alternating current with frequencies up to 20 kHz and above .....	20
4.6.4 Direct current.....	21
4.7 Value of the initial resistance of the human body ( $R_0$ ) .....	22
4.8 Characteristics of the impedance of the body of livestock .....	22
5 Effects of sinusoidal alternating current in the range of 15 Hz to 150 Hz.....	22
5.1 General.....	22
5.2 Threshold of perception .....	22
5.3 Threshold of reaction .....	22
5.4 Immobilization.....	22
5.5 Threshold of let-go.....	23
5.6 Threshold of ventricular fibrillation .....	23
5.7 Other effects related to electric shocks .....	23
5.8 Effects of current on the skin .....	24
5.9 Description of time/current zones (see Figure 20) .....	24
5.10 Application of heart-current factor ( $F$ ).....	25
6 Effects of direct current .....	26
6.1 General.....	26
6.2 Threshold of perception and threshold of reaction.....	26
6.3 Threshold of immobilization and threshold of let-go.....	26
6.4 Threshold of ventricular fibrillation .....	26
6.5 Other effects of current .....	27
6.6 Description of time/current zones (see Figure 22) .....	27
6.7 Heart factor.....	28
6.8 Effects of anodic versus cathodic DC currents .....	45
Annex A (normative) Measurements of the total body impedances $Z_T$ made on living human beings and on corpses and statistical analysis of the results .....	48
Annex B (normative) Influence of frequency on the total body impedance ( $Z_T$ ).....	51

Annex C (normative) Total body resistance ( $R_T$ ) for direct current.....	52
Annex D (informative) Examples of calculations of $Z_T$ .....	53
Annex E (informative) Theories of ventricular fibrillation.....	56
Annex F (informative) Quantities of upper limit of vulnerability (ULV) and lower limit of vulnerability (LLV) .....	57
Annex G (informative) Circuit simulation methods in electric shock evaluation .....	58
Annex H (normative) Effects of currents passing through the body of livestock .....	61
H.1 General.....	61
H.2 Principal consideration of the risk of ventricular fibrillation for livestock .....	61
H.3 Characteristics of the impedance of the body of livestock .....	62
H.4 Internal impedance of animals ( $Z_i$ ) .....	62
H.5 Impedance of the hide and skin ( $Z_P$ ).....	63
H.6 Impedance (resistance) of the hoof ( $Z_h$ , $R_h$ ).....	63
H.7 Total body impedance ( $Z_T$ ) .....	63
H.8 Initial body resistance ( $R_0$ ).....	64
H.9 Values of the total body impedance ( $Z_T$ ) .....	64
H.10 <b>This is a preview. Click here to purchase the full publication.</b> .....	65
H.11 Effects on livestock of sinusoidal alternating current in the range from 15 Hz to 100 Hz .....	65
H.11.1 General .....	65
H.11.2 Threshold of reaction .....	66
H.11.3 Threshold of ventricular fibrillation .....	66
Bibliography.....	69
Figure 1 – Impedances of the human body.....	28
Figure 2 – Internal partial impedances $Z_{ip}$ of the human body.....	29
Figure 3 – Simplified schematic diagram for the internal impedances of the human body .....	30
Figure 4 – Total body impedance $Z_T$ (50 %) for a current path hand to hand, for large surface areas of contact in dry, water-wet and saltwater-wet conditions for a percentile rank of 50 % of the population for touch voltages $U_T = 25$ V to 700 V, AC 50/60 Hz .....	31
Figure 5 – Dependence of the total impedance $Z_T$ of one living person on the surface area of contact in dry conditions and at touch voltage (50 Hz) .....	32
Figure 6 – Dependence of the total body impedance $Z_T$ on the touch voltage $U_T$ for a current path from the tips of the right to the left forefinger compared with large surface areas of contact from the right to the left hand in dry conditions measured on one living person, touch voltage range $U_T = 25$ V to 200 V, AC 50 Hz, duration of current flow max. 25 ms.....	33
Figure 7 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in dry conditions at touch voltages $U_T = 25$ V to 200 V AC 50/60 Hz.....	34
Figure 8 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in water-wet conditions at touch voltages $U_T = 25$ V to 200 V, AC 50/60 Hz .....	35
Figure 9 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V, AC 50/60 Hz.....	36

Figure 10 – Values for the total body impedance $Z_T$ measured on 10 living human beings with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 10 V and frequencies from 25 Hz to 20 kHz .....	37
Figure 11 – Values for the total body impedance $Z_T$ measured on one living human being with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 25 V and frequencies from 25 Hz to 2 kHz .....	37
Figure 12 – Frequency dependence of the total body impedance $Z_T$ of a population for a percentile rank of 50 % for touch voltages from 10 V to 1 000 V and a frequency range from 50 Hz to 150 kHz for a current path hand to hand or hand to foot, large surface areas of contact in dry conditions .....	38
Figure 13 – Statistical value of total body impedances $Z_T$ and body resistances $R_T$ for a percentile rank of 50 % of a population of living human beings for the current path hand to hand, large surface areas of contact, dry conditions, for touch voltages up to 700 V, for AC 50/60 Hz and DC .....	38
Figure 14 – Dependence of the alteration of human skin condition on current density $i_T$ and duration of current flow .....	39
Figure 15 – Electrodes used for the measurement of the dependence of the impedance of the human body $Z_T$ on the surface area of contact .....	40
Figure 16 – Measurements of the dependence of the impedance of the human body $Z_T$ on the surface area of contact .....	41
Figure 17 – Occurrence of the vulnerable period of ventricles during the cardiac cycle .....	42
Figure 18 – Triggering of ventricular fibrillation in the vulnerable period – Effects on electro-cardiogram (ECG) and blood pressure .....	42
Figure 19 – Fibrillation data for dogs, pigs and sheep from experiments and for persons calculated from statistics of electrical accidents with transversal direction of current flow hand to hand and touch voltages $U_T = 220$ V and 380 V AC with body impedances $Z_T$ (5 %) .....	43
Figure 20 – Conventional time/current zones of effects of AC currents (15 Hz to 100 Hz) on persons for a current path corresponding to left hand to feet (see Table 11) .....	44
Figure 21 – Oscillogram of touch voltages $U_T$ and touch current $I_T$ for DC, current path hand to hand, large surface areas of contact in dry conditions .....	44
Figure 22 – Conventional time/current zones of effects of DC currents on persons for a longitudinal upward current path (see Table 13) .....	45
Figure 23 – Let-go currents for 60 Hz sinusoidal current .....	45
Figure 24 – Effects of anodic versus cathodic DC currents .....	46
Figure 25 – Pulsed DC stimulation of single heart cells .....	47
Figure G.1 – Electric shock in electrical model by Hart [33] including startle reaction effect .....	59
Figure H.1 – Current flow and impedances of the relevant parts of the body of a cow for current path from the nose to the legs .....	62
Figure H.2 – Diagrams for an animal, for a current path from the nose to the four legs (path A) and from the forelegs to the hindlegs (path B) .....	62
Figure H.3 – Diagram for the total body impedance for cattle for a percentage of 5 % of the population .....	65
Figure H.4 – Ventricular fibrillation for sheep .....	66
Figure H.5 – Minimum fibrillating currents of sheep as a function of weight for a shock duration of 3 s [55] .....	67
Figure H.6 – Minimum fibrillating currents (averages) of various species of livestock as a function of weight for a shock duration of 3 s [53] .....	68
Table 1 – Total body impedances $Z_T$ for a current path hand to hand AC 50/60 Hz, for large surface areas of contact in dry conditions .....	15

**This is a preview. Click here to purchase the full publication.**



Table 2 – Total body impedances $Z_T$ for a current path hand to hand AC 50/60 Hz, for large surface areas of contact in water-wet conditions .....	16
Table 3 – Total body impedances $Z_T$ for a current path hand to hand AC 50/60 Hz, for large surface areas of contact in saltwater-wet conditions .....	17
Table 4 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in dry conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $25 \Omega$ ) .....	18
Table 5 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in water-wet conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $25 \Omega$ ) .....	19
Table 6 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $5 \Omega$ ) .....	19
Table 7 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in dry conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $25 \Omega$ ) .....	19
Table 8 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $5 \Omega$ ) .....	20
Table 9 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25 \text{ V}$ to $200 \text{ V}$ AC 50/60 Hz (values rounded to $5 \Omega$ ) .....	20
Table 10 – Total body resistances $R_T$ for a current path hand to hand, direct current, for large surface areas of contact in dry conditions .....	21
Table 11 – Time/current zones for AC 15 Hz to 100 Hz for hand to feet pathway – Summary of zones of Figure 20 .....	25
Table 12 – Heart-current factor $F$ for different current paths .....	26
Table 13 – Time/current zones for direct current for hand to feet pathway – Summary of zones of Figure 22 .....	28
Table A.1 – Total body impedances $Z_T$ , electrodes type A for dry conditions and deviation factors $F_D$ (5 % and 95 %) .....	48
Table A.2 – Total body impedances $Z_T$ , electrodes type B for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %) .....	48
Table A.3 – Total body impedances $Z_T$ for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %) .....	48
Table A.4 – Deviation factors $F_D$ (5 %) and $F_D$ (95 %) for dry and water-wet conditions in the touch voltage range $U_T = 25 \text{ V}$ up to $400 \text{ V}$ for large, medium and small surface areas of contact .....	50
Table D.1 – 50 <sup>th</sup> percentile values for the total body impedance for a current path hands-feet, medium surface area of contact for hands, large for feet, reduction factor 0,8, dry conditions, touch currents $I_T$ and electrophysiological effects .....	54
Table G.1 – Body impedance examples (uncompensated) .....	59
Table H.1 – Impedance (resistance) of the hooves of cattle ( $Z_h$ , $R_h$ ) for AC voltages up to $230 \text{ V}$ , 50/60 Hz .....	63
Table H.2 – Total body impedances $Z_T$ for AC 50/60 Hz for cattle for touch voltages up to $230 \text{ V}$ .....	64
Table H.3 – Initial body resistance $R_0$ for cattle .....	65
Table H.4 – Threshold of ventricular fibrillation for AC 50/60 Hz [53] [54] for different species of livestock, for a shock duration of 3 s .....	67

**This is a preview. Click here to purchase the full publication.**